

IN THE CLAIMS

1-7 (Canceled).

8. (Original) A method for testing a liquid crystal display panel, comprising:

loading a unit liquid crystal display panel on a first table including first, second, third and fourth testing bars; and

measuring a distance between the longer sides of the unit liquid crystal display panel while operating the first and second testing bars and a distance between the shorter sides of the unit liquid crystal display panel while operating the third and fourth testing bars.

9. (Original) The method of claim 8, further comprising testing for burr defect on at least one of the longer and shorter sides of the unit liquid crystal display panel.

10. (Original) The method of claim 9, wherein the testing includes testing whether or not the burr is remained on the longer sides of the unit liquid crystal display panel using the first and second testing bars.

11. (Original) The method of claim 9, wherein the testing includes testing whether or not the burr is remained on the shorter sides of the unit liquid crystal display panel using the third and fourth testing bars.

12. (Original) The method of claim 9, wherein testing includes testing whether or not the burr is remained on the longer sides and on the shorter sides of the unit liquid crystal display panel using the first to fourth testing bars at the same time.

13. (Original) The method of claim 8, further comprising:

cutting a plurality of liquid crystal display panels into unit liquid crystal display panels prior to loading a unit liquid crystal display panel.

14. (Original) The method of claim 9, wherein testing at least one of the longer and shorter sides of the unit liquid crystal display panel includes checking a cut edge of the unit liquid crystal display panel.

15. (Original) The method of claim 14, wherein checking the cut edge is performed by touching at least one of the first, second, third and fourth testing bars to the cut edge of the unit liquid crystal display panel.

16. (Original) The method of claim 8, wherein the first and third testing bars have a step shape.

17. (Original) The method of claim 16, wherein at least one of the longer and shorter sides of the unit liquid crystal display panel engage with the step shape of at least one of the first and third testing bars.

18. (Original) The method of claim 8, wherein measuring a distance between the longer sides and a distance between the shorter sides is performed using a gauge.

19. (Original) The method of claim 8, wherein the unit liquid crystal display panel includes a color filter substrate on a thin film transistor array substrate.

20. (Original) A method for testing a liquid crystal display panel, comprising:

loading a unit liquid crystal display panel on a first table including first and second testing bars; and

testing for defect on opposite sides of the unit liquid crystal display panel using the first and second testing bars and at the same time measuring a distance of at least one side of the unit liquid crystal display panel.

21. (Original) The method of claim 20, wherein one of the first and second testing bars includes position sensors and wherein the measuring comprises measuring the distance of the at least one side of the unit liquid crystal display panel using the position sensors.

22. (Original) The method of claim 20, wherein the first and second testing bars include optical sensors and wherein the measuring comprises measuring a distance of the at least one side of the unit liquid crystal display panel using the optical sensors.

23. (Original) The method of claim 22, wherein the optical sensors includes a light source on one of the first and second testing bars and a photo detector on the other of the first and second testing bars wherein the measuring comprises measuring the intensity of light received by the photo detector from the light source.